

Ferotec Friction, Inc.
 150 Shellyland Road Rapho Business Park
 PO Box 387 Mount Joy, PA 17552

Material Safety	D9715		Data Sheet	
Telephone: (717) 492-9600		Revision Date: 9/01/06		Fax: (717) 492-9601
I. Product Information:				
Product Name: D9715				
Trade Name: Flow molded non-asbestos product with high friction and good wear qualities.				
II. NFPA (0 = No Hazard; 4 = Severe Hazard):				
Health = 1		Reactivity = 0		Fire = 1
III. Ingredient Information:				
Hazardous Components	C.A.S. Number	Percent	OSHA PEL (mg/m³)	ACGIH TLV (mg/m³)
*Antimony Trioxide	1309-64-4	1-5	.5	.5
Fiberglass	65997-17-3	3-10	15	10
Graphite	7782-42-5	4-15	10	10
Phenolic Resin	Mixture	12-20	Not Listed	Not Listed
*Copper Oxide	1317-38-0	6-11	1	1
The above chemicals marked with an asterisk (*) are subject to Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Part 372 Part C-Supplier Notification Requirement.				
IV. Physical Data:				
Boiling Point (°F):	NA	Evaporation Rate (Butyl Acetate = 1)		NA
Vapor Pressure (mm Hg):	NA	Specific Gravity (Water = 1):		2.60
Water Solubility (%):	NA	Melting Point (°F):		NA
Vapor Density (Air = 1):	NA	% Volatile by Volume:		NA
Appearance And Odor:	Dark gray rigid product with little or no odor			
V. Fire and Explosion Data:				
Flash Point (°F):	NA	Flammable Limits: LEL = NA UEL = NA		
Extinguishing Media:	Water, foam, dry chemical		Unusual Fire and Explosion Hazards: None	
Special Fire Fighting Procedures:	In a sustained fire, self-contained breathing apparatus (SCBA) should be worn.			
VI. Health Data: A. Summary/Risks:				
<u>Continuous Filament Fiberglass:</u> Inadequate evidence of carcinogenicity in both human and animal scientific studies to link this fiber to human cancer. Therefore, classified as Group 3.				
Clinical Conditions Which May Be aggravated: Any condition generally aggravated by mechanical irritants in air or on skin.				
Target Organs:	Lungs, skin.			
Acute Health Effects:	Temporary irritation of the mouth, nose, and throat.			
Chronic Health Effects:	Designated by IARC as "not classifiable as to human carcinogenicity." Not listed by NPT or by OSHA.			
Primary Routes of Entry:	Inhalation			

Material Safety	D9715	Data Sheet
VI. Health Data: B. Signs/Symptoms of Overexposure:		
Inhalation:	May cause temporary upper respiratory irritation.	
Skin Contact:	Acute - Transient mechanical irritation. Chronic - None.	
Ingestion:	Acute - Unlikely to occur. Observe individual, if symptoms develop, consult physician. Chronic - None known.	
Eyes:	Acute - Direct contact will cause mechanical irritation. Chronic - None known.	
VI. Health Data: C. First Aid/Emergency Procedures:		
Inhalation:	Remove from exposure. Get medical help if irritation persists.	
Skin Contact:	Wash with mild soap and running water.	
Ingestion:	Unlikely. Consult physician if unusual reaction is noted.	
Eyes:	Flush with flowing water for at least 15 minutes. If symptoms persist, seek immediate medical attention.	
VII. Reactivity Data:		
Conditions to Avoid:	Avoid creating dust. Vacuum when possible.	
Hazardous Decomposition Products:	Incomplete combustion may release toxic materials.	
VIII. Spill or Leak Procedures:		
Procedures for Spill/Leak:	Use vacuum if dust is involved.	
Waste Management:	In accordance with state and local regulations.	
IX. Special Protection Information:		
Goggles:	May be appropriate in certain operations.	
Gloves:	May reduce skin irritation in some operations.	
Respirator:	NIOSH approved nuisance dust respirator if TLV is exceeded.	
Ventilation:	Use local exhaust ventilation.	
Other:	Wear long sleeved shirts, loose fitting clothing and use good personal hygiene.	
Special Consideration for Repair & Maintenance of Contaminated Equipment:	NA	
X. Special Considerations:		
Special Handling/Storage:	Store in a dry place. Label information: "Any fiber or dust may be a hazard to your health. Use respirators and/or dust control measures as well as eye protection when handling or processing this product. Do not ingest."	
Other:	Wash with mild soap and warm water after handling. Wash work clothes separately.	
<i>The information and recommendations set forth herein are taken from sources believed to be accurate as of the date thereof; however, Ferotec Friction makes no warranty with respect to the accuracy of the information or the suitability of the recommendations and assumes no liability to any user thereof.</i>		